

Full Function

H.264 Standalone DVR

UH 1300 Series 8 CH /16 CH



Support Safari Netviewing for Mac users

Remote Surveillance via Internet Explorer & Mozilla Firefox also available



Mac



Product Highlight

>> **CD/DVDRW Backup & PTZ Control**
>> **Video covert**

- Real-Time Recording
- Daylight Saving Time
- Email Notification For Events
- Selectable Display Resolution
 - 1280 X 1024
 - 1024 X 768
 - 800 X 600
- NTP (Network Time Protocol)
- Adjustable Fan Speed
- Snap Shot
- Multi-language Editable Camera Title
- Auto Zoom For Composite Output



(Optional)



(Optional)

>> **Keyboard control up to 8 DVRs**



www.ultracker.com

Widen your vision

Specification

UH1300 Series



Model	UH1308	UH1316	
Function	No. of cameras	8	16
	Split display mode	1,4,9	1,4,9,16
	Image output	Dynamic video display	
	Multiplex mode	Pentaplex (Live/ Record/ Playback/ Backup/ Network)	
	Display resolution	1280x1024, 1024x768, 800x600	
	Picture per second	Display:1/4/9 60/120/240 fps (NTSC) 50/100/200 fps (PAL)	Display:1/4/9/16 60/120/240/480 fps (NTSC) 50/100/200/400 fps (PAL)
	Color	16 M colors (Y:8, U:8, V:8) 4:2:2	
	Sequence	2 sets	3 sets
	PTZ control		Yes
	Daylight saving time		Yes
	Adjustable fan speed		Yes
	Watch dog		Yes
	Multi-language editable camera title		Yes
	Auto zoom for composite output		Yes
	3D Deinterlace		Yes
	3D Noise Reduction		Yes
	Bicubic Smoother		Yes
	Playback mark		Yes
Record	Resolution	NTSC: 640x480, 640x240, 320x240 PAL: 640x512, 640x256, 320x256	
	FPS	240 fps(NTSC), 200 fps(PAL)	480 fps(NTSC), 400 fps(PAL)
	Recording quality	5 levels	
	H.264 enhanced	Yes	
	Average compression rate	More than 300:1	
	Programmable Schedule	Yes	
	Motion recording	Yes	
	Pre-recording	3 sec ~ 5sec	
	Post-recording	1 sec ~ 255 sec (programmable)	
Playback	Search mode	Smart search by file/ event/ frame/ time/ date	
	Search speed	Date, hour, min, sec, frame, pause	
	Playback speed	Pause, x1, x5, x15, x60	
Connector	Video in BNC	8	16
	Video out DVI		x1
	Video out VGA		x1
	Video out BNC		x1
	Audio in		RCA x2
	Audio out		RCA (L, R)
	Ethernet 10/100M		RJ45 x1
	RS-485		RJ11 x1
	Keyboard		RJ11 x1
	DC Jack		1
	Alarm Port	1 (Alarm-in x16, Alarm-out x3, Relay-out x1)	
	USB Port	x2 (Mouse x1, USB flash drive x1)	
	IR Remote Controller		Yes
Alarm/ Motion	Motion detection	1200 motion zones	
	Motion detection sensitivity	100 levels	
	No. of alarm outputs	3	
	No. of alarm inputs	16	
	Alarm Type	NO (Normal Open), NC (Normal Close), relay	
Event	Size of events list	8192 events per disk	
	Event source	Alarm, motion, video loss, power on/off, discontinued record, mark USB	
Ethernet	10/100M LAN	Yes	
	Remote viewing	IE / Firefox, suggested resolution: 1024x768	
	PPPoE	Yes	
	DHCP	Yes	
	DDNS	Yes	
	Email notification for events	Yes	
	NTP (Network Time Protocol)	Yes	
HDD	Internal SATA bay	2	
	Size of hard drive	120GB ~ 2000GB	
Backup	USB flash drive	Yes	
	CD/DVDRW	Yes	
	Snap shot	Yes	
	Remote backup	Yes	
Specification	Voltage	DC19 Voltage	
	Voltage range	100~240V	
	Power MAX	60W	
	Operating temperature	5~ 40 °C	
	Operating relative humidity	10~75 %	
	Net weight	5.5 KG	
	Shipping weight	6KG	
	DVR Dimension (mm)	432 x 67 x 280 (W x H x D)	